


**1 Identification of the substance and manufacturer**

Trade name: PROTEK® S316 STAINLESS STEEL COATING  
 Product code: 538  
 Recommended use: Paint and coating applications.  
 Uses advised against: Any that differs from the recommended use.  
 Manufacturer/Supplier: PR Distribution  
 6500, rue Zéphirin Paquet  
 Quebec, QC G2C 0M3  
 1800-463-5259  
 www.prdistribution.ca  
 Emergency telephone number: CANUTEC 1-888-CAN-UTEC (226-8832)

**2 Hazard(s) identification****Classification of the substance or mixture**

Flam. Aerosol 1 H222 Extremely flammable aerosol.  
 Press. Gas H280 Contains gas under pressure; may explode if heated.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 Repr. 1 H360 May damage fertility or the unborn child.  
 STOT SE 3 H336 May cause drowsiness or dizziness.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

**GHS Hazard pictograms**

GHS02 GHS04 GHS07 GHS08

**Signal word****Hazard statements**

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May damage fertility or the unborn child.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash hands thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Precautionary statements****3 Composition/information on ingredients****Chemical characterization: Mixtures****Chemical Description:**

This product is a mixture of the substances listed below with nonhazardous additions.

**Dangerous components:**

67-64-1	Acetone	25.48%
74-98-6	propane	15.74%
110-19-0	Isobutyl Acetate	9.4%
106-97-8	n-butane	9.25%
123-86-4	butyl acetate	9.21%
1330-20-7	xylene (mix)	6.89%
65997-19-5	Stainless Steel Flake	6.1%
108-88-3	Toluene	5.33%
100-41-4	ethyl benzene	1.22%
64742-47-8	Mineral Spirits	1.08%

**4 First-aid measures****After inhalation:**

Supply fresh air; consult doctor in case of complaints.

**After skin contact:**

Remove contaminated clothing. Wash exposed area with soap and water.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:**

Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects:**

Dizziness

## Safety Data Sheet

Revised On 05/02/2018

Trade name: PROTEK® S316 STAINLESS STEEL COATING

**Indication of any immediate medical attention needed:**

No further relevant information available.

(Contd. of page 1)

**5 Fire-fighting measures****Extinguishing agents:**CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray.**Special hazards:**

Can form explosive gas-air mixtures.

**Protective equipment for firefighters:**

A respiratory protective device may be necessary.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

**Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

**7 Handling and storage****Precautions for safe handling**

Use only in well ventilated areas.

**Storage requirements:**

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**PEL (USA) Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 590 mg/m<sup>3</sup>, 250 ppmTLV (USA) Short-term value: 1187 mg/m<sup>3</sup>, 500 ppmLong-term value: 594 mg/m<sup>3</sup>, 250 ppm  
BEI**74-98-6 propane**PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppmREL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) refer to Appendix F in TLVs&amp;BEIs book; D, EX

**110-19-0 Isobutyl Acetate**PEL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppmREL (USA) Long-term value: 700 mg/m<sup>3</sup>, 150 ppmTLV (USA) Short-term value: 712 mg/m<sup>3</sup>, 150 ppmLong-term value: 238 mg/m<sup>3</sup>, 50 ppm**106-97-8 n-butane**REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppmTLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm  
(EX)**123-86-4 butyl acetate**PEL (USA) Long-term value: 710 mg/m<sup>3</sup>, 150 ppmREL (USA) Long-term value: 950 mg/m<sup>3</sup>, 200 ppmTLV (USA) Short-term value: 712 mg/m<sup>3</sup>, 150 ppmLong-term value: 238 mg/m<sup>3</sup>, 50 ppm**1330-20-7 xylene (mix)**PEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL (USA) Short-term value: 655 mg/m<sup>3</sup>, 150 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV (USA) Short-term value: 651 mg/m<sup>3</sup>, 150 ppmLong-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

**108-88-3 Toluene**PEL (USA) Long-term value: 200 ppm  
Ceiling limit value: 300; 500\* ppm  
\*10-min peak per 8-hr shiftREL (USA) Short-term value: 560 mg/m<sup>3</sup>, 150 ppmLong-term value: 375 mg/m<sup>3</sup>, 100 ppmTLV (USA) Long-term value: 75 mg/m<sup>3</sup>, 20 ppm

BEI

**100-41-4 ethyl benzene**EL (USA) Long-term value: 20 ppm  
IARC 2BPEL (USA) Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL (USA) Short-term value: 545 mg/m<sup>3</sup>, 125 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV (USA) Long-term value: 87 mg/m<sup>3</sup>, 20 ppm

BEI

(Contd. on page 3)

## Safety Data Sheet

Revised On 05/02/2018

Trade name: PROTEK® S316 STAINLESS STEEL COATING

(Contd. of page 2)

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA) 50 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

**1330-20-7 xylene (mix)**

BEI (USA) 1.5 g/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: Methylhippuric acids

**100-41-4 ethyl benzene**

BEI (USA) 0.7 g/g creatinine  
 Medium: urine  
 Time: end of shift at end of workweek  
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
 Medium: end-exhaled air  
 Time: not critical  
 Parameter: Ethyl benzene (semi-quantitative)

**Hygienic protection:**

Immediately remove all soiled and contaminated clothing.  
 Wash hands after use.  
 Store protective clothing separately.  
 Avoid contact with the eyes and skin.  
 Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas.  
 In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.

**Eye protection:**

The glove material must be impermeable and resistant to the substance.  
 Tightly sealed goggles

**9 Physical and chemical properties**

**Appearance:** Aerosol.  
**Odor:** Aromatic  
**Odor threshold:** Not determined.  
**pH-value:** Not determined.  
**Melting point/Melting range** Undetermined.  
**Boiling point:** -44 °C (-47.2 °F)  
**Flash point:** -19 °C (-2.2 °F)  
**Flammability (solid, gas):** Extremely flammable.  
**Decomposition temperature:** Not determined.  
**Auto igniting:** Product is not self-igniting.  
**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.  
**Lower Explosion Limit:** 1.7 Vol %  
**Upper Explosion Limit:** 10.9 Vol %  
**Vapor pressure:** Not determined.  
**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)  
**Vapor density** Not determined.  
**Evaporation rate** Not applicable.  
**Partition coefficient: n-octanol/water:** Not determined.  
**Solubility:** Not determined.  
**Viscosity:** Not determined.  
**Water:** 0.0 %

**10 Stability and reactivity**

**Reactivity:** Stable at normal temperatures.  
**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.  
**Chemical stability:** Not fully evaluated.  
**Possibility of hazardous reactions:** No dangerous reactions known.  
**Incompatible materials:** No further relevant information available.  
**Hazardous decomposition:** No dangerous decomposition products known.

**11 Toxicological information****LD/LC50 values that are relevant for classification:****110-19-0 Isobutyl Acetate**

Oral	LD50	4,763 mg/kg (rbt)
------	------	-------------------

**106-97-8 n-butane**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

(Contd. on page 4)

## Safety Data Sheet

Revised On 05/02/2018

Trade name: PROTEK® S316 STAINLESS STEEL COATING

(Contd. of page 3)

**123-86-4 butyl acetate**

Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)

**1330-20-7 xylene (mix)**

Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	6,350 mg/l (rat)

**100-41-4 ethyl benzene**

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rbt)

**Information on toxicological effects:** No data available.  
**Skin effects:** No irritant effect.  
**Eye effects:** Irritating effect.  
**Sensitization:** No sensitizing effects known.

**12 Ecological information**

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

**UN-Number** UN1950  
**DOT** N/A  
**DOT** Consumer Commodity ORM-D  
 Aerosols, flammable  
 1950 Aerosols  
**ADR**  
**Transport hazard class(es):**  
**Class** 2.1  
**Special precautions for user:** Warning: Gases  
**EMS Number:** F-D,S-U  
**Stowage Code** SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  
**Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.  
**Quantity limitations** On passenger aircraft/rail: 75 kg  
 On cargo aircraft only: 150 kg  


---

**ADR**  
**Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity  


---

**IMDG**  


---

**Limited quantities (LQ)** 1L  
**Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity  
**Packaging Group:** --  
**UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene (mix)
108-88-3	Toluene
100-41-4	ethyl benzene

**Toxic Substances Control Act (TSCA):**

All hazardous ingredients for this product are found on the inventory list of substances.

**Consumer Product Safety Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

(Contd. on page 5)

## Safety Data Sheet

Revised On 05/02/2018

Trade name: PROTEK® S316 STAINLESS STEEL COATING

(Contd. of page 4)

**California Proposition 65 chemicals known to cause cancer:**

100-41-4 ethyl benzene

**California Proposition 65 chemicals known to cause birth defects or reproductive harm:**

108-88-3 Toluene

**CANADIAN ENVIRONMENTAL  
PROTECTION ACT:  
WHMIS Symbols for Canada:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A - Compressed gas

D2A - Very toxic material causing other toxic effects

**Canadian WHMIS:**

D2A

**EPA:**

67-64-1	Acetone	I
110-19-0	Isobutyl Acetate	D
1330-20-7	xylene (mix)	I
100-41-4	ethyl benzene	D

**USDA (United States Department of  
Agriculture):**

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact.

**16 Other information****Contact:**

Regulatory Affairs

Date of preparation / last revision

05/02/2018 / -