

Safety Data Sheet

Battery Terminal Protector

SECTION 1. IDENTIFICATION

Product Identifier	Battery Terminal Protector
Part number	629
Product Family	Solvent blend
Recommended Use	Protectant.
Restrictions on Use	None known.
Supplier Identifier	PR Distribution Inc., 6500, rue Zéphirin-Paquet, Quebec, QC, G2C 0M3, 418.872.6018, www.prdistribution.ca
Emergency Phone No.	CANUTEC, +1.613.996.6666, Operation hours: 24/7

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable aerosol - Category 1; Gas under pressure - Compressed gas; Skin irritation - Category 2; Specific target organ toxicity (single exposure) - Category 3; Aspiration hazard - Category 1

Label Elements



Danger

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Pressurized container: may burst if heated.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Keep away from heat, sparks, open flames, and hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing spray, vapours.

Wash hands and skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTRE or doctor if you feel unwell.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents and container in accordance with local, regional, national and international regulations.

Product Identifier: Battery Terminal Protector

SDS No.: 629

Page 01 of 07

Date of Preparation: November 17, 2016

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers
Toluene	108-88-3	30-60	
Petroleum gases, liquefied, sweetened	68476-86-8	15-40	

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Remove source of exposure or move to fresh air. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by Poison Centre or doctor. If breathing has stopped, trained personnel should begin rescue breathing. Immediately call a Poison Centre or doctor.

Skin Contact

Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. If skin irritation occurs, get medical advice or attention.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists, get medical advice or attention.

Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. Drink two glasses of water. Immediately call a Poison Centre or doctor.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide or dry chemical. Use water to keep non-leaking, fire-exposed containers cool.

Unsuitable Extinguishing Media

DO NOT use water or water-based extinguishing agents.

Specific Hazards Arising from the Product

Contains gas under pressure; may explode if heated. Extremely flammable aerosol. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, resulting in a fire hazard. May travel a considerable distance to a source of ignition and flash back to a leak or open container.

Carbon oxides, and other unidentified organic compounds.

Special Protective Equipment and Precautions for Fire-fighters

Fight fire from a safe distance or a protected location. Use extreme caution.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Do not touch damaged containers or spilled product unless wearing appropriate protective equipment. Evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. May accumulate in hazardous amounts in low-lying areas especially inside confined spaces, if ventilation is not sufficient. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Remove or isolate incompatible materials as well as other hazardous materials.

Environmental Precautions

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Do not

Product Identifier: Battery Terminal Protector

SDS No.: 629

Date of Preparation: November 17, 2016

allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Contain and soak up spill with absorbent that does not react with spilled product. Contaminated absorbent poses the same hazard as the spilled product. Place used absorbent into suitable, covered, labelled containers for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not spray on an open flame or other ignition source. Do not pierce or burn container, even after use. Do not weld, cut or perform hot work on empty container until all traces of product have been removed. Do NOT smoke in work areas. It is good practice to: avoid breathing product; avoid skin and eye contact and wash hands after handling. Only use where there is adequate ventilation.

Conditions for Safe Storage

Store in an area that is: cool, dry, well-ventilated, out of direct sunlight and away from heat and ignition sources. Store at temperatures not exceeding: 40°C.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH® TLV®		OSHA PEL	
	TWA	STEL [C]	TWA	Ceiling
Toluene	20 ppm A4	Not established	Not established	Not established

Appropriate Engineering Controls

Sufficient mechanical ventilation to maintain exposures below the TLV. Under normal conditions of use, general ventilation should be satisfactory. Local ventilation is recommended if the product is misted or used in a confined space or if the TLV is exceeded. Make up air should always be supplied to balance air exhausted. Provide eyewash in work area, if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Safety glasses with side shields.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Suitable materials are: butyl rubber, nitrile rubber.

Respiratory Protection

Not normally required if product is used as directed.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Dark blue Aerosol.
Odour	Not available
Odour Threshold	Not available
pH	Not applicable
Melting Point/Freezing Point	Not available (melting)
Initial Boiling Point/Range	Not available
Flash Point	26 °C (closed cup)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable aerosol
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)

Product Identifier: Battery Terminal Protector

SDS No.: 629

Date of Preparation: November 17, 2016

Vapour Pressure	Not available
Vapour Density (air = 1)	> 1
Relative Density (water = 1)	0.922 at 15 °C
Solubility	Insoluble in water
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	< 14 centistokes at 40°C (kinematic)
Other Information	
VOC %	Not available
Flame projection	< 100 cm flashback
NFPA Classification	Aerosol, level 3 flashback

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None expected under normal conditions of storage and use.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources.

Incompatible Materials

Increased risk of fire and explosion on contact with: strong oxidizing agents (e.g. perchloric acid).

Hazardous Decomposition Products

Carbon oxides. And other unidentified organic compounds.

SECTION 11. TOXICOLOGICAL INFORMATION

Information presented below is for the entire product, unless otherwise specified.

Likely Routes of Exposure

Inhalation;
Skin contact;
Eye contact;
Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Toluene	7585 ppm (rat) (4-hour exposure)	5580 mg/kg (male rat)	12125 mg/kg (rabbit)

37% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (inhalation)

37% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (oral)

37% of the mixture consists of an ingredient or ingredients of unknown acute toxicity (dermal)

Skin Corrosion/Irritation

There is limited evidence of moderate or severe irritation.

Serious Eye Damage/Irritation

There is limited evidence of very mild irritation.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

At high concentrations may cause nose and throat irritation. Symptoms may include headache, nausea, dizziness, drowsiness and confusion.

Ingestion

If large amounts are swallowed may cause Can cause effects as described for inhalation.

Aspiration Hazard

May cause lung damage if aspirated based on physical properties (e.g. kinematic viscosity) and chemical family (hydrocarbon).

STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause effects on the central nervous system.

Respiratory and/or Skin Sensitization

No information was located.

Carcinogenicity

Chemical Name	ACGIH®	IARC	NTP	OSHA
Toluene	A4	Group 3	Not Listed	Not Listed

Not a carcinogen.

Reproductive Toxicity

Development of Offspring

(Toluene) may cause effects on the unborn child based on limited evidence.

No information was located for: Sexual Function and Fertility, Effects on or via Lactation, Germ Cell Mutagenicity, Interactive Effects

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Empty containers retain product residue. Follow label warnings even if container appears to be empty. The container for this product can present explosion or fire hazards, even when emptied. Do not cut, puncture, or weld on or near this container. Dispose of in accordance with municipal, provincial/state or federal regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	UN1950	Aerosols	2.1	---
IMDG (Marine)	UN1950	Aerosols	2.1	---
IATA (Air)	UN1950	Aerosols, flammable	2.1	---
US DOT	UN1950	Aerosols	2.1	---

Special Precautions Not applicable

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Product Identifier: Battery Terminal Protector

SDS No.: 629

Date of Preparation: November 17, 2016

Emergency Response 126 EmS F-D, S-U
Guide No.

Other Information ICAO/IATA PI Y203/203
Product may ship as LTD QTY if TDG, ICAO/IATA or IMDG Limited Quantity provisions are met.

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

CEPA - National Pollutant Release Inventory (NPRI)

(Toluene) Part 1A.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

CERCLA. (Toluene)

SARA Title III - Section 302: Not applicable.

SARA Title III - Section 313. (Toluene)

California Proposition 65. (Toluene)

Massachusetts Right To Know: Not applicable.

New Jersey Right To Know. (Toluene)

Pennsylvania Right To Know. (Toluene)

SECTION 16. OTHER INFORMATION

NFPA Rating	Health - 1	Flammability - 4	Instability - 3
SDS Prepared By	Regulatory Compliance		
Phone No.	800.201.9486		
Date of Preparation	November 17, 2016		
Key to Abbreviations	ACGIH® = American Conference of Governmental Hygienists CANUTEC = Canadian Transport Emergency Centre CAS = Chemical Abstract Service CCOHS = Canadian Centre for Occupational Health & Safety CNS = Central nervous system GESTIS = GESTIS Substance Database HSDB® = Hazardous Substances Data Bank IARC = International Agency for Research on Cancer ICAO = International Civil Aviation Organization IMDG = International Maritime Dangerous Goods Code LC = Lethal concentration LD = Lethal dose NFPA = National Fire Protection Association NTP = National Toxicology Program OSHA = US Occupational Safety and Health Administration PPM = Parts per million RTECS® = Registry of Toxic Effects of Chemical Substances STEL = Short term exposure limit TDG = Transportation of Dangerous Goods Regulations (Canada) TWA = Time weighted average		
References	Material safety data sheet from manufacturer.		

Product Identifier: Battery Terminal Protector

SDS No.: 629

Date of Preparation: November 17, 2016

CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).
HSDB® database. US National Library of Medicine. Available from Canadian Centre for Occupational Health and Safety (CCOHS).
Registry of Toxic Effects of Chemical Substances (RTECS®) database. Accelrys, Inc. Available from Canadian Centre for Occupational Health and Safety (CCOHS).
ECHA - European Chemical Agency, Classification and Labelling Inventory
GESTIS Substance Database
OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.

Disclaimer

The information contained herein is offered only as a guide to the use and handling of this specific material and has been prepared in good faith. It is not intended to be all-inclusive, and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied. Shrader Canada Limited will not be liable for any damages, losses, injuries or consequential damages which may result from the use of or reliance on any information contained herein.